


# DigiTrace MONI-PT100-EXE TEMPERATURE SENSOR FOR HAZARDOUS AREAS 🐼



3 wire Pt 100 sensor connected to a black glass fiber reinforced polyester junction box with 4 front entry springtype terminals.

M20 EEx e cable gland preinstalled.

# **AREA OF USE**

Hazardous environment Zone I

### **APPROVALS**

Baseefa11ATEX0068X

#### **SENSOR**

Mounting

Туре	Pt 100 (3 wire) DIN IEC 751, Class B.
Material	extension cable and tip both stainless steel (MI)
Temperature measuring range	-100°C to +500°C
Maximum exposure temp. tip	+585°C
Length	2 m
Diameter	ca 3 mm
Minimum bending radius	extension cable: 20 mm, the measuring tip should not be bent
ENCLOSURE	
Material	Glass fiber reinforced polyester (black)
Ingress protection	IP66
Dimensions	With = 80 mm Height = 75 mm Depth = 55 mm
Cable entry	M20 (EEx e) suitable for cable diameters ranging from 10 mm to 14 mm
Operating temperature	+55°C to +60°C
Sealing gasket material	tongue and groove system with silicone seal
Cover screws	Stainless steel M4 threaded

For pipe mount use JB-SB-26 wall mount surface mount via moulded holes at 68 x 45 mm

# MONI-PT100-EXE

Terminals	4 front entry spring-type terminals	
Terminal sizing	suitable for cables from 0.5 mm <sup>2</sup> to 2.5 mm <sup>2</sup>	
ORDERING DETAILS		
Part Description	MONI-PT100-EXE	



## EUROPE, MIDDLE EAST, AFRICA

Tel: +32.16.213.511 Fax: +32.16.213.603 thermal.info@pentair.com

# UNITED KINGDOM

Tel: 0800 969 013 Fax: 0800 968 6241 salesthermaluk@pentair.com IRELAND

Tel: 1800 654 241 Fax: 1800 654 240 salesie@pentair.com

All Pentair trademarks and logos are owned by Pentair. All other brand or product names are trademarks or registered marks of their respective owners. Because we are continuously improving our products and services, Pentair reserves the right to change specifications without prior notice. Pentair is an equal opportunity employer.

© 2013 Pentair. All Rights Reserved.

WWW.PENTAIRTHERMAL.COM